

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
14 July 2005 (14.07.2005)

PCT

(10) International Publication Number  
**WO 2005/062797 A2**

(51) International Patent Classification: **Not classified**

(21) International Application Number:  
PCT/US2004/042503

(22) International Filing Date:  
17 December 2004 (17.12.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:  
60/531,336 19 December 2003 (19.12.2003) US

(71) Applicant and

(72) Inventor: **SCHYMURA, Margarete** [US/US]; 2350  
Broadway, New York, NY 10024 (US).


(74) Agent: **FALLER, F., Brice**; Cohen Pontani Lieberman &  
Pavane, 551 Fifth Avenue, New York, NY 10176 (US).

(81) Designated States (*unless otherwise indicated, for every kind of national protection available*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (*unless otherwise indicated, for every kind of regional protection available*): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

[Continued on next page]

(54) Title: PICTURE FRAME ASSEMBLY FOR MOUNTING TO A CYLINDRICAL OBJECT



(57) Abstract: A picture frame assembly includes a backing plate having a front surface, a rear surface, and a plurality of parallel grooves in one of the surfaces. The material and thickness of the backing plate are chosen so that the backing plate may be plastically deformed about a bending axis parallel to the grooves. At least one frame element, which may be formed integrally with the backing plate, is provided for retaining a planar picture element against the front surface of the backing plate. A pair of tack elements extending from the rear surface are provided for mounting the assembly to a cylindrical object such as a tree or a candle.

WO 2005/062797 A2



**Published:**

— without international search report and to be republished  
upon receipt of that report

*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*